FRONTIER MEDICAL SCREENS FLEXES CERTIFICATE





Confidential Report

Our Ref: Supplement to E-005905



Notified Body for PPE Directive, Construction Products Regulation & Marine Equipment Directive I.D. No. 0338 & 0339



Unit 6, Wheel Forge Way, Trafford Park, Manchester, M17 1EH, UK.

> Telephone: +44 (0) 161 876 4211 Email: info@bttg.co.uk

> > Website: www.bttg.co.uk

Date: 17 October 2018

Our Ref: Supplement to

E-005905 Your Ref: --

Page: 1 of 4

Client: Camira Fabrics Limited

The Watermill
Wheatley Park
Mirfield
West Yorkshire
WF14 8HE

Job Title: Flexing on two samples

Client's Order No: 83A00946

Date of Receipt: 5th October 2018
Date of Test Start: 10th October 2018

Description of Sample(s): Two samples of fabric identified as follows, were received for testing:

Call 8348, Vita (C), Colour: Yellow
 Call 8348, Vita (C), Colour: Pink

Work Requested: We were asked to make the following test on each sample:

Schildknecht Flexing ISO 7854: 1997 Method B





Unit 6, Wheel Forge Way, Trafford Park,

Email: info@bttg.co.uk Website: www.bttg.co.uk

Manchester, M17 1EH, UK. Telephone: +44 (0) 161 876 4211

> 17 October 2018 Date:

Our Ref: Supplement to E-005905

Your Ref:

Page: 2 of 4

Camira Fabrics Limited

Samples were identified as follows:

1) Call 8348, Vita (C), Colour: Yellow 2) Call 8348, Vita (C), Colour: Pink

Laboratory Work

The tests were made in Standard Atmosphere (65 ± 4 % relative humidity at 20 ± 2°C) the samples having been freely and continuously exposed to that atmosphere for at least 24 hours prior to testing. Specimens have been taken from the samples as described in the specified standard.

Resistance to Damage by Flexing

Flex cracking resistance was tested following the procedure in Method B - Schildknecht method, of BS EN ISO 7854: 1997 (BS 3424: Part 9: 1996), "Rubber- or plastics-coated fabrics - Determination of resistance to damage by flexing". Three specimens, in each direction, were tested for a predetermined number of cycles.

At the clients' request, the specimens were to be inspected at 400 000 cycles.

The flexing damage was assessed according to the following methods.

The overall appearance of the specimens was assessed for deterioration considering all visible factors such as wrinkling, cracking, flaking and discolouration. Specimens were graded, without magnification, using the 4 part numerical scale.

Each specimen was examined, under magnification, to determine depth, length and number of cracks. Depth of cracking was assessed using the descriptive scale. The length of the longest crack (mm) and the number of cracks have been reported.

The results for all tests are given in the table on the following page.

Mrs S Jones Laboratory Technician

Mr P Hutchings Operational Head

Note: This report relates only to the samples submitted and as described in the report.





Unit 6, Wheel Forge Way, Trafford Park, Manchester, M17 1EH, UK. Telephone: +44 (0) 161 876 4211

Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 17 October 2018

Our Ref: Supplement to E-005905

Your Ref: --

Page: 3 of 4

Camira Fabrics Limited

RESULTS

Sample Ref 1: Call 8348, Vita (C), Colour: Yellow

| ASSESSMENT OF SCHILDKNECHT FLEX DAMAGE AT 400 000 CYCLES | | | | | | |
|--|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Specimen Number | 1 (Length) | 2 (Length) | 3 (Length) | 4 (Width) | 5 (Width) | 6 (Width) |
| Deterioration in Appearance | 2 | 2 | 2 | 2 | 2 | 2 |
| Type of damage (if any) | Moderate creasing |
| Depth of Cracking | А | Α | А | Nil | А | А |
| Number of Cracks Of The Lowest Grade | 4* | 4 | 5* | 0 | 1 | 2 |
| Length Of Longest Crack of The Lowest Grade (mm) | 4* | 1 | 2* | N/A | 1 | 1 |

^{*}Note: numerous small cracks forming larger cracks.

| Deterioration In appearance | | Dept | Depth of Cracking | | |
|-----------------------------|----------|------|--|--|--|
| 0 | None | Nil | no cracking | | |
| 1 | Slight | Α | surface or finish crack, not exposing the cellular or middle layer | | |
| 2 | Moderate | В | cracking into but not right through the middle layer, or, in the case of single-layer coatings, not exposing the base fabric | | |
| 3 | Severe | С | cracking through to the base fabric | | |
| | | D | cracking right through the material | | |





Unit 6, Wheel Forge Way, Trafford Park, Manchester, M17 1EH, UK. Telephone: +44 (0) 161 876 4211

Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 17 October 2018

Our Ref: Supplement to E-005905

Your Ref: ---

Page: 4 of 4

Camira Fabrics Limited

RESULTS

Sample Ref 2: Call 8348, Vita (C), Colour: Pink

| ASSESSMENT OF SCHILDKNECHT FLEX DAMAGE AT 400 000 CYCLES | | | | | | |
|--|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Specimen Number | 1 (Length) | 2 (Length) | 3 (Length) | 4 (Width) | 5 (Width) | 6 (Width) |
| Deterioration in Appearance | 2 | 2 | 2 | 2 | 2 | 2 |
| Type of damage (if any) | Moderate creasing |
| Depth of Cracking | Nil | А | Nil | Α | Nil | А |
| Number of Cracks Of The Lowest Grade | 0 | 10 | 0 | 2 | 0 | 2 |
| Length Of Longest Crack of The Lowest Grade (mm) | N/A | 1 | N/A | 1 | N/A | 1 |

| Deteriora | ation In appearance | Dept | h of Cracking |
|-----------|---------------------|------|--|
| 0 | None | Nil | no cracking |
| 1 | Slight | Α | surface or finish crack, not exposing the cellular or middle layer |
| 2 | Moderate | В | cracking into but not right through the middle layer, or, in the case of single-layer coatings, not exposing the base fabric |
| 3 | Severe | С | cracking through to the base fabric |
| | | D | cracking right through the material |

